

Specifications

Model	KT4K32-3568BS	KT4K43-3568BS	KT4K49-3568BS	KT4K55-3568BS	KT4K65-3568BS	KT4K75-3568BS	KT4K86-3568BS
Screen Size (Diagonal)	32 inch	43 inch	49 inch	55 inch	65 inch	75 inch	86inch
Native Resolution	FHD	3840 (H) × 2160 (V)					
Aspect Ratio	16 : 9						
Brightness	700 nit (Typ.)						
Contrast	≥ 1200:1						
View Angle	178 ° (H) / 178 ° (V)						
Display Color	16.7M						
Response Time	14ms						
Operation Time	24/7						
Life Time (Light Source)	50,000 Hrs (Typ.)						
Surface treatment	25% Haze						
HDMI IN 2.0	×1						
AV IN	×1 (3.5mm Earphone)						
USB 2.0	× 2						
AUDIO_OUT	500mVRMS(MAX) × 1						
RS232	× 1						
RJ45	× 1						
TF Card	× 1						
CPU	RK3568, ARM Cortex-A55 2.0Ghz						
GPU	Mali-G52 GPU						
RAM	2GB						
OS	Android 11						
LAN	Up to 1000M ethernet						
WIFI	Support 2.4G/5G wifi 6, 802. 11 a/b/g/n/ac/ax						
Bluetooth	Bluetooth 5.0						
Power supply	AC 100-20V 50~60hz						
Power consumption	120W	157W	163W	165W	190W	247W	350W
Power	<0.5W	<0.5W	<0.5W	<0.5W	<0.5W	<0.5W	<0.5W
Operation Temperature	0°C~45°C						
Operation Humidity	10%-85%						
Storage Temperature	-20°C~60°C						
Storage Humidity	5%-95%						
Color/Material	Black/Aluminum						
Bezel Width	6mm	6mm	6mm	6mm	7.9mm	7.9mm	7.9mm
Outline Dimension (W×H×D)mm	711.7×408.7 ×61.7	956.2×546.2 ×61.7	1088×619.1 ×61.7	1224.6×698 ×61.7	1444.5×821 ×61.7	1665.7×946. 4×61.9	1917. 1×108 8. 1×62.1
Package Dimension (W×H×D)mm	830* 145*57 5	1115*209*7 00	1243*209*7 73	1379*209*8 53	1598*209*9 74	1819*209* 1 100	2099*224* 1 262
Net Weight	6KG	8.5KG	9.8KG	11.9KG	15.9KG	21KG	30KG
Packed Weight (1 Sets	12KG	16KG	18. 1KG	21.3KG	28.4KG	35.2KG	53KG
VESA Mounting	200 X 200	400× 200	400× 300	400× 300	400× 400	400× 400	600× 400