


HIGH BRIGHTNESS WINDOW FACING DISPLAY SPEC								
Picture								
Model No.	Series	KGI32DTH	KGI43DTH	KGI49DTH	KGI55DTH	KGI65DTH	KGI75DWH	KGI86DWH
Cabinet.	Material	Metal						
	Color	Black						
	Dimensions	731.8*55*426.3mm	974.6*55.5*562.8mm	1107.2*55.5* 637.4mm	1242.9*55.5*713.8mm	1461.8*55.5*836.9mm	1676.5*67.5*954.7mm	1958*66.4*1129mm
	Vesa	200*200mm	400*400mm	400*400mm	400*400mm	400*400mm	600*400mm	650*700mm
	Net.Weight	8.5kg	13kg	15.8kg	20kg	29kg	38kg	52kg
LCD Panel	Screen Diagonal	32inch	43inch	49inch	55inch	65inch	75inch	86inch
	Resolution (H x V)	1920*1080	3840*2160	3840*2160	3840*2160	3840*2160	3840*2160	3840*2160
	Contrast(Typical)	1200:1	1200:1	1300:1	1200:1	1100:1	1200:1	1200:1
	Brightness(Typical)	2500cd/m2	2500cd/m2	2500cd/m2	2500cd/m2	2500cd/m2	2500cd/m2	2500cd/m2
	Display Color	8 bits, 16.7M	8 bits, 16.7M	8 bits, 16.7M	8 bits, 16.7M	8 bits, 16.7M	8 bits, 16.7M	8 bits, 16.7M
	Response Time(Typical)	6.5ms	6.5ms	6.5ms	6.5ms	6.5ms	6.5ms	6.5ms
	View Angles LR, UD(CR>10)	178°/178°	178°/178°	178°/178°	178°/178°	178°/178°	178°/178°	178°/178°
Backlight rated hours	≥50000hours	≥50000hours	≥50000hours	≥50000hours	≥50000hours	≥50000hours	≥50000hours	
System	Solution	Android 11						
Configuration	CPU	RK3568, Quad-core,up to 2.0 GHz						
	GPU	Mali-G52						
	RAM	2GB						
	Storage Device	32GB						
	Network	1000 Mbps Ethernet, Wi-Fi, Bluetooth 5.0						
	Interface	1*HDMI in, 1x RJ45, 2*USB , Earphone out, etc						
Support	Video	H.265, H.264, VP8, MAV , WMV , AVS , H.263, MPEG4,etc						
	Music	MP3, WMA, WAV, APE, FLAC, AAC, OGG, M4A, 3GPP, etc						
	Photo	JPG、JPEG、 BMP、 PNG、 GIF						
Power	AC Power Range	100-240V AC,50/60HZ						
	Rated Consumption	≅ 55W	≅ 157W	≅ 200W	≅ 355W	≅ 385W	≅ 440W	≅ 950W
	Standby Consumption	≅ 1W	≅ 1W	≅ 1W	≅ 1W	≅ 1W	≅ 1W	≅ 1W
Operating Condition	Working Temperature	-10 C ~60 C						
Feature	On Screen Display	English etc.						
	Power On when plugged in	Yes						
Accessory	Built-in Speaker	2*5W						
	Power Cable	1.8 meters						
Others	APP Control	Mobile APP wireless control, no need server						
	Internet Remote Control	Support Free Cloud-Based management						
	Highly Integrated	Integrated Wi-Fi/ Ethernet/USB/TF/infrared remote control interface						
	Multiple Communication Method	Support multiple program update methods: U-Disk/TF Card/Wi-Fi/Ethernet/Cloud						
Packing Info	Carton size	870*200*560mm	1120*200*720mm	1255*200*780mm	1395*200*850mm	1605*200*960mm	1850*240*1170mm	2100*240*1290mm
	G/W	13kg	19kg	23kg	28kg	39kg	52kg	70kg